


*1: Photo changeable
 - V : Silver
 - E : Red
 - G : Gold
 H : White Silver



Model				ARNU07GSF*2	ARNU09GSF*2	ARNU12GSF*2
Capacity	Cooling	Nom	kW	2.2	2.8	3.6
	Heating	Nom	kW	2.5	3.2	4.0
Power Input	Cooling	Nom	W	35	35	35
	Heating	Nom	W	35	35	35
Power Supply	ø/V/Hz			1 / 220 ~240 / 50	1 / 220 ~240 / 50	1 / 220 ~240 / 50
Airflow Rate	Cooling	H/M/L	m ³ /min	8.1 / 6.3 / 4.2	8.1 / 6.3 / 4.2	9.3 / 7.7 / 6.0
	Heating	H/M/L	m ³ /min	8.1 / 6.3 / 4.2	8.1 / 6.3 / 4.2	9.3 / 7.7 / 6.0
Sound Pressure	H/M/L		dB	38 / 32 / 27	38 / 32 / 27	44 / 38 / 32
Dimensions	Body	WxDxH	mm	600 x 600 x 146	600 x 600 x 146	600 x 600 x 146
Net Weight				15(33.1)	15(33.1)	15(33.1)
Piping Connection	Liquid			6.35(1/4)	6.35(1/4)	6.35(1/4)
	Gas			12.7(1/2)	12.7(1/2)	12.7(1/2)
	Drain	I.D.	mm(inch)	12.2(15/32)	12.2(15/32)	12.2(15/32)

Note :

1. Capacities are based on the following conditions

Cooling - Indoor temp. 27°C(80.6°F)DB / 19°C(66.2°F)WB
 Outdoor temp. 35°C(95°F)DB / 24°C(75.2°F)WB
 Interconnecting piping length 7.5m
 Level difference of zero

Heating - Indoor temp. 20°C(68°F)DB / 15°C(59°F)WB
 Outdoor temp. 7°C(44.6°F)DB / 6°C(42.8°F)WB
 Interconnecting piping length 7.5m
 Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

Accessories

Model		ARNU07GSF*2	ARNU09GSF*2	ARNU12GSF*2
Dry Contact	Without Case (1 Contact Point)		PQDSA	
	With Case (1 Contact Point)		PQDSB / PQDSB1	
	With Case (2 Contact Point)		PQDSBC	

Wired Remote Controller				Wireless Remote Controller
Standard Type	Standard Type	Simple Type	Simple Type for Hotel	
PQRCUDSO	PQRCVSL0QW	PQRCVCL0Q (Black) PQRCVCL0QW (white)	PQRCHCA0Q (Black) PQRCHCA0QW (White)	PQWRHQ0FDB