

SPLIT OUTDOOR UNIT (3Ø 400V)



Outdoor Unit			HU123. U31	HU143. U31	HU163. U31
Combined Hydrokit			HN1616. NK1 HN1626. NK1 HN1636. NK1 HN1629. NK1 HN1639. NK1		
Power Supply			ø / V / Hz		
			3ø / 380-415V / 50Hz		
Nominal Capacity	Heating(A10/W35)	kW	13.25	15.06	17.34
	Heating(A7/W35)	kW	12	14	16
	Heating(A2/W35)	kW	9.46	10.89	12.22
	Heating(A-7/W35)	kW	11.66	12.72	14.92
	Cooling(A35/W18)	kW	14.60	15.50	16.80
Nominal Input	Heating(A10/W35)	kW	3.02	3.49	4.1
	Heating(A7/W35)	kW	2.72	3.24	3.81
	Heating(A2/W35)	kW	2.83	3.28	3.82
	Heating(A-7/W35)	kW	4.31	4.98	5.95
	Cooling(A35/W18)	kW	4.02	4.65	5.09
COP	Heating(A10/W35)	W/W	4.39	4.32	4.23
	Heating(A7/W35)	W/W	4.41	4.32	4.20
	Heating(A2/W35)	W/W	3.34	3.32	3.20
	Heating(A-7/W35)	W/W	2.71	2.55	2.51
EER	Cooling(A35/W18)	W/W	3.63	3.33	3.30
Sound pressure level	Heating	dBA	53		
	Cooling	dBA	54		
Dimension	W*H*D	mm	950*1,380*330		
Weight		kg	105		
Refrigerant (R410A)	Pre-charged amount	g	2,980		
	Pipe Diameter(Liquid/Gas)	inch	3/8, 5/8		