

Floor Standing with Case

ARNU07GCEA2 ARNU09GCEA2 ARNU12GCEA2
ARNU15GCEA2 ARNU18GCEA2 ARNU24GCEA2



Model		ARNU07GCEA2	ARNU09GCEA2	ARNU12GCEA2	ARNU15GCEA2	ARNU18GCEA2	ARNU24GCEA2
Capacity	Cooling Nom kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating Nom kW	2.5	3.2	4.0	5.0	6.3	8.0
Power Input	Cooling Nom W	30	30	30	30	80	80
	Heating Nom W	30	30	30	30	80	80
Power Supply	ø/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Airflow Rate	Cooling H/M/L m ³ /min	8.5 / 7.5 / 6.5	9.5 / 8.5 / 7.5	10.5 / 9.5 / 8.5	11.5 / 10.0 / 9.5	16.0 / 14.0 / 12.0	18.0 / 16.0 / 14.0
	Heating H/M/L m ³ /min	8.5 / 7.5 / 6.5	9.5 / 8.5 / 7.5	10.5 / 9.5 / 8.5	11.5 / 10.0 / 9.5	16.0 / 14.0 / 12.0	18.0 / 16.0 / 14.0
Sound Pressure	H/M/L dBA	35 / 33 / 31	36 / 34 / 32	37 / 35 / 33	38 / 37 / 35	40 / 37 / 34	43 / 40 / 37
Dimensions	Body WxDxH mm	1,067 x 635 x 203	1,067 x 635 x 203	1,067 x 635 x 203	1,067 x 635 x 203	1,345 x 635 x 203	1,345 x 635 x 203
Net Weight	Liquid kg(lbs)	27(59.5)	27(59.5)	27(59.5)	27(59.5)	34(75.0)	34(75.0)
	Gas mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	9.52(3/8)
Piping Connection	Gas mm(inch)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	15.9(5/8)
	Drain I.D. mm(inch)	12(15/32)	12(15/32)	12(15/32)	12(15/32)	12(15/32)	12(15/32)

Note :

1. Capacities are based on the following conditions


Cooling - Indoor temp. 27°C(80.6°F)DB / 19°C(66.2°F)WB
Outdoor temp. 35°C(95°F)DB / 24°C(75.2°F)WB
Interconnecting piping length 7.5m
Level difference of zero

Heating - Indoor temp. 20°C(68°F)DB / 15°C(59°F)WB
Outdoor temp. 7°C(44.6°F)DB / 6°C(42.8°F)WB
Interconnecting piping length 7.5m
Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

Floor Standing without Case

ARNU07GCEU2 ARNU09GCEU2 ARNU12GCEU2
ARNU15GCEU2 ARNU18GCEU2 ARNU24GCEU2



Model		ARNU07GCEU2	ARNU09GCEU2	ARNU12GCEU2	ARNU15GCEU2	ARNU18GCEU2	ARNU24GCEU2
Capacity	Cooling Nom kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating Nom kW	2.5	3.2	4.0	5.0	6.3	8.0
Power Input	Cooling Nom W	30	30	30	30	80	80
	Heating Nom W	30	30	30	30	80	80
Power Supply	ø/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Airflow Rate	Cooling H/M/L m ³ /min	8.5 / 7.5 / 6.5	9.5 / 8.5 / 7.5	10.5 / 9.5 / 8.5	11.5 / 10.0 / 9.5	16.0 / 14.0 / 12.0	18.0 / 16.0 / 14.0
	Heating H/M/L m ³ /min	8.5 / 7.5 / 6.5	9.5 / 8.5 / 7.5	10.5 / 9.5 / 8.5	11.5 / 10.0 / 9.5	16.0 / 14.0 / 12.0	18.0 / 16.0 / 14.0
Sound Pressure	H/M/L dBA	35 / 33 / 31	36 / 34 / 32	37 / 35 / 33	38 / 37 / 35	40 / 37 / 34	43 / 40 / 37
Dimensions	Body WxDxH mm	978 x 639 x 190	978 x 639 x 190	978 x 639 x 190	978 x 639 x 190	1,256 x 639 x 190	1,256 x 639 x 190
Net Weight	Liquid kg(lbs)	20(44.1)	20(44.1)	20(44.1)	20(44.1)	27(59.5)	27(59.5)
	Gas mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	9.52(3/8)
Piping Connection	Gas mm(inch)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	15.9(5/8)
	Drain I.D. mm(inch)	12(15/32)	12(15/32)	12(15/32)	12(15/32)	12(15/32)	12(15/32)

Note :

1. Capacities are based on the following conditions

Cooling - Indoor temp. 27°C(80.6°F)DB / 19°C(66.2°F)WB
Outdoor temp. 35°C(95°F)DB / 24°C(75.2°F)WB
Interconnecting piping length 7.5m
Level difference of zero

Heating - Indoor temp. 20°C(68°F)DB / 15°C(59°F)WB
Outdoor temp. 7°C(44.6°F)DB / 6°C(42.8°F)WB
Interconnecting piping length 7.5m
Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

Accessories

Model	ARNU07GCEA2	ARNU09GCEA2	ARNU12GCEA2	ARNU15GCEA2	ARNU18GCEA2	ARNU24GCEA2
Without Case (1 Contact Point)	PQDSA					
With Case (1 Contact Point)	PQDSB / PQDSB1					
With Case (2 Contact Point)	PQDSBC					

Wired Remote Controller					Wireless Remote Controller
Deluxe Type	Standard Type	Standard Type	Simple Type	Simple Type for Hotel	
PQRCUDS0(white) PQRCUDS0B(blue) PQRCUDS0S(silver)	PQRCVSL0	PQRCVSL0QW	PQRCVCL0Q (Black) PQRCVCL0QW (white)	PQRCVCL0QW (white) PQRCVCL0QW (White)	PQWRHQ0FDB

Accessories

Model	ARNU07GCEU2	ARNU09GCEU2	ARNU12GCEU2	ARNU15GCEU2	ARNU18GCEU2	ARNU24GCEU2
Without Case (1 Contact Point)	PQDSA					
With Case (1 Contact Point)	PQDSB / PQDSB1					
With Case (2 Contact Point)	PQDSBC					

Wired Remote Controller					Wireless Remote Controller
Deluxe Type	Standard Type	Standard Type	Simple Type	Simple Type for Hotel	
PQRCUDS0(white) PQRCUDS0B(blue) PQRCUDS0S(silver)	PQRCVSL0	PQRCVSL0QW	PQRCVCL0Q (Black) PQRCVCL0QW (white)	PQRCVCL0QW (White) PQRCVCL0QW (White)	PQWRHQ0FDB