

SPLIT OUTDOOR UNIT (1Ø 230V)



Outdoor Unit			HU091. U41
Combined Hydrokit			
			HN0916. NK1 HN0926. NK1 HN0936. NK1 HN0914. NK1
Power Supply	ø/ V / Hz		1ø / 220-240V / 50Hz
Nominal Capacity	Heating(A10/W35)	kW	9.71
	Heating(A7/W35)	kW	9
	Heating(A2/W35)	kW	6.87
	Heating(A-7/W35)	kW	8.61
	Cooling(A35/W18)	kW	9.00
Nominal Input	Heating(A10/W35)	kW	2.2
	Heating(A7/W35)	kW	2.2
	Heating(A2/W35)	kW	2.07
	Heating(A-7/W35)	kW	3.19
	Cooling(A35/W18)	kW	2.65
COP	Heating(A10/W35)	WW	4.41
	Heating(A7/W35)	WW	4.09
	Heating(A2/W35)	WW	3.32
	Heating(A-7/W35)	WW	2.70
EER	Cooling(A35/W18)	WW	3.40
Sound pressure level	Heating	dBA	52
	Cooling	dBA	52
Dimension	W*H*D	mm	950*834*330
Weight		kg	64
Refrigerant (R410A)	Pre-charged amount	g	1,900
	Pipe Diameter(Liquid/Gas)	inch	3/8, 5/8