


1 Way Cassette

ARNU07GTUC2 ARNU09GTUC2
ARNU12GTUC2 ARNU18GTTC2 ARNU24GTTC2



Grill Type

Model				ARNU07GTUC2	ARNU09GTUC2	ARNU12GTUC2	ARNU18GTTC2	ARNU24GTTC2
Capacity	Cooling	Nom	kW	2.2	2.8	3.6	5.6	7.1
	Heating	Nom	kW	2.5	3.2	4.0	6.3	7.1
Power Input	Cooling	Nom	W	40	40	40	70	70
	Heating	Nom	W	40	40	40	70	70
Power Supply			ø/V/Hz	1 / 220 ~240 / 50	1 / 220 ~240 / 50	1 / 220 ~240 / 50	1 / 220 ~240 / 50	1 / 220 ~240 / 50
Airflow Rate	Cooling	H/M/L	m³/min	8.2 / 7.3 / 6.4	9.2 / 8.6 / 8.2	10 / 9.2 / 8.2	13.3 / 12.1 / 10.9	14.6 / 13.3 / 11.5
	Heating	H/M/L	m³/min	8.2 / 7.3 / 6.4	9.2 / 8.6 / 8.2	10 / 9.2 / 8.2	13.3 / 12.1 / 10.9	14.6 / 13.3 / 11.5
Sound Pressure			dBA	32 / 29 / 25	35 / 34 / 32	38 / 35 / 32	40 / 37 / 35	43 / 40 / 36
Dimensions	Body	WxHxD	mm	860 x 450 x 132	860 x 450 x 132	860 x 450 x 132	1,180 x 450 x 132	1,180 x 450 x 132
Net Weight			kg(lbs)	14.7(32.4)	14.7(32.4)	14.7(32.4)	18.7(41.23)	18.7(41.23)
Piping Connection	Liquid		mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	9.52(3/8)
	Gas		mm(inch)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	15.88(5/8)
	Drain	I.D.	mm(inch)	25(31/32)	25(31/32)	25(31/32)	25(31/32)	25(31/32)
Decoration Panel	Model			PT-UUC(Grill), PT-UUD(Panel)	PT-UUC(Grill), PT-UUD(Panel)	PT-UUC(Grill), PT-UUD(Panel)	PT-UTC(Grill), PT-UTD(Panel)	PT-UTC(Grill), PT-UTD(Panel)
	Colour			White	White	White	White	White
	Dimensions	WxDxH	mm	1,100 x 34 x 500	1,100 x 34 x 500	1,100 x 34 x 500	1,420 x 34 x 500	1,420 x 34 x 500
	Weight		kg	4.6	4.6	4.6	5.5	5.5

Note :

1. Capacities are based on the following conditions

Cooling - Indoor temp. 27°C(80.6°F)DB / 19°C(66.2°F)WB
Outdoor temp. 35°C(95°F)DB / 24°C(75.2°F)WB
Interconnecting piping length 7.5m
Level difference of zero

Heating - Indoor temp. 20°C(68°F)DB / 15°C(59°F)WB
Outdoor temp. 7°C(44.6°F)DB / 6°C(42.8°F)WB
Interconnecting piping length 7.5m
Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

INDOOR UNITS

Accessories

Model	ARNU07GTUC2	ARNU09GTUC2	ARNU12GTUC2	ARNU18GTTC2	ARNU24GTTC2
Dry Contact	Without Case (1 Contact Point)		PQDSA		
	With Case (1 Contact Point)		PQDSB / PQDSB1		
	With Case (2 Contact Point)		PQDSBC		

Wired Remote Controller					Wireless Remote Controller
Deluxe Type	Standard Type	Standard Type	Simple Type	Simple Type for Hotel	
PQRCUDS0(white) PQRCUDSOB(blue) PQRCUDS0S(silver)	PQRCVSLO	PQRCVSLQW	PQRCVCLQQ (Black) PQRCVCLQW (white)	PQRCVCLQW (white)	PQWRHQ0FDB